

BALL VALVES

0642EN March 2020

VALVE FOR WATER FOR HEATING/COOLING SYSTEMS
AND NOT DANGEROUS GAS
FULL PORT - R859 SERIES



GIACOMINI
WATER E-MOTION



R859

Description

Ball valve, with female-tail piece male threaded connections.
Full port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color
R859X323	G 1/2"F x R 1/2"	Chrome plated brass	T-handle	Red
R859X325	G 3/4"F x G 3/4"M	Chrome plated brass	T-handle	Red
R859X327	G 1"F x G 1"M	Chrome plated brass	T-handle	Red
R859X329	G 1-1/4"F x G 1-1/4"M	Chrome plated brass	T-handle	Red
R859X343	G 1/2"F x R 1/2"	Chrome plated brass	T-handle	Blue
R859X345	G 3/4"F x G 3/4"M	Chrome plated brass	T-handle	Blue
R859X347	G 1"F x G 1"M	Chrome plated brass	T-handle	Blue
R859X349	G 1-1/4"F x G 1-1/4"M	Chrome plated brass	T-handle	Blue

Technical data

Main features and materials


- Suitable for water for heating/cooling systems and not dangerous gas
- Full port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium T-handle, red or blue painted

Field of applications

- Min. working temperature: -20 °C with 50 % glycol solutions
- Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar)
- Max. working pressure at 20 °C with water and not dangerous gas: 3,5 MPa (35 bar) for 1/2", 3/4" 2,8 MPa (28 bar) for 1", 1-1/4"

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	H' [mm]	Kv
R859X323	15	74	27	54	16	63	wr.25	wr.30	12,7
R859X325	20	83	30	64	20	73	wr.31	wr.38	24,6
R859X327	25	95	31	72	24	73	wr.38	wr.46	48,5
R859X329	32	112	42	82	30	73	wr.47	wr.53	98,0
R859X343	15	74	27	54	16	63	wr.25	wr.30	12,7
R859X345	20	83	30	64	20	73	wr.31	wr.38	24,6
R859X347	25	95	31	72	24	73	wr.38	wr.46	48,5
R859X349	32	112	42	82	30	73	wr.47	wr.53	98,0



Product specifications

R859

Ball valve, with female-tail piece male threaded connections. Suitable for water for heating/cooling systems and not dangerous gas. Valve made of UNI EN 12165 CW617N chrome plated brass. Full port. Aluminium T-handle, red or blue painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Min. working temperature: -20 °C with 50 % glycol solutions. Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar). Max. working pressure at 20 °C with water and not dangerous gas: 3,5 MPa (35 bar) for 1/2", 3/4"; 2,8 MPa (28 bar) for 1", 1-1/4".

Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy